

ICON™

A LANDOLL® Company

- ✓ Max durability, operator friendly control, 21 cubic heaped yards while maintaining a narrow 11 ft. 11 inch transport width, rapid patented eject, super duty Quickhitch, and a combination of innovative features and benefits not found on any other scraper!

821 PULL TYPE SCRAPER

21 cu. yds., under 12 ft. transport width and the most features and benefits available in a pull type scraper



- ✓ The durable, functional, and eye appealing design of the ICON **821** gives the contractor a cost effective machine with profitable return on investment and a strong resale value for the future.
- ✓ The **821** Scraper is fully assembled, lubed, filled with hydraulic oil, and checked at the factory before shipping, making the machine ready for the job on delivery to the customer. After 36 to 48 hours on the job, a quick check and adjustments are then made by dealer service.
- ✓ The **821** has a six-month Warranty, limited to a 600-engine horsepower rubber track or tire-pulling tractor.

- ✓ The durability designed into the **821** starts at the front of the machine with the ICON Quickattach cast hitch. Convenience and safety are built into this 360-degree swivel hitch with one-man mount/dismount and rollover protection.



- ✓ Tandem configuration capability with Quickhitch on the rear of the lead scraper for rapid and safe, one-man mount/dismount. Operator site gauge sets the rear machine for proper ground engagement. Two valve sequencing hydraulics for rapid operation and operator friendly control. Epoxy lined bowl with clean, quick, patented Swingwall eject.

ICON Industries, Inc.

1600 W. 8th Street • Beloit, Kansas 67420
(785)738-6613 • www.iconindinc.com

ICON reserves the right to change models, designs, and/or specifications without notice or obligation. Additional information on the back of this page.




ICON

A LANDOLL® Company

- ✓ Industrial cylinders and 4000-psi hydraulic hoses throughout the scraper provide rapid response and longevity.
- ✓ The front gate and eject wall are finished in dirt rejecting epoxy and feature the ICON patented Swingwall eject for rapid and clean cycles.
- ✓ The rear assembly of the **821** includes a host of features and benefits, such as two large 20.5 x 25 16-ply earthmover inside tires and two 23.5 x 25 outside tires providing over 80 total inches width of rubber on an offset design, creating a dual plane footprint for maximum flotation and controlled haul roads.
- ✓ Cushioning the haul is accomplished by a hydraulic accumulator.
- ✓ Hydraulic operation of the gate and wall is controlled by a synchro-sequencing valve.
- ✓ Double wall design, high tensile steel where needed, and a 21 cubic yard max capacity provide durability and productivity.

- ✓ Narrow transport, 11 ft. 11 inches, allows for safe and reasonably priced hauling to and from the job site.
- ✓ Hydraulic disc brakes are standard on the **821**.



- ✓ Operator reference gauge in the cab with digital readout provides precise reference to the bowl/gate settings. For single or tandem operation.



ICON Industries, Inc.

1600 W. 8th Street • Beloit, Kansas 67420
(785)738-3547 • www.iconindinc.com

ICON reserves the right to change models, designs, and/or specifications without notice or obligation.

